

MX-701

Network Type : LV

Digital multimeter TRMS

Application:

- Measures DC and AC voltages, DC and AC current, resistance, inductance, temperature.
- Test of diodes and open circuits (audible alarm).
- DC voltage: 600 mV - 1 000 V.
- AC voltage: 600 mV - 750 V.
- DC current: 600 μ A - 10 A.
- AC current : 600 μ A - 10 A.
- Resistance: 600 Ω - 60 M Ω .
- Continuity : buzzer (>60 W).
- Capacitance: 10 nF - 100 mF

Features:

- Temperature (with the temperature probe): -20°C-1 000°C/ -4°F-1 800°F.
- Impact resistant elastomeric shell.
- True RMS response.
- Continuity & Diode test
- LCD display with backlight
- Data hold
- Non contact function NCV
- High voltage LED indication
- Flashlight enables measurements in dark easier
- Auto power off
- Battery: 2 x 1,5 V (AA)
- Dimensions: 188 x 88 x 54 mm
- Weight: 320 g (with battery)

Composition :

- 2 test probes with angled connector IP2X
- 1 thermometric probe



Ref	Dimensions		Weight	Voltages for use		Continuity Test
	Length (mm)			Operating Voltage AC	Operating Voltage DC	
MX-701	186		0,3	600 mV - 750 V	600 mV - 1 000 V	<60 Ω